


# Thermal Detection Module

Helping to create  
Peace of Mind In Public  
Spaces





# CONTACTLESS – MAINTAIN SOCIAL DISTANCING PROTOCOLS

This is a contactless method of skin temperature screening, allowing safe indication while maintaining Social Distancing requirements

## Works in Seconds


Within 2 seconds our Thermal Detection Module is able to screen employees for signs of elevated skin temperature and alert the staff member or customer using infrared light



## Stand options & Accessories



Tall Stand



Counter Stand

## Adjustable Mounts

Comes with a Adjustable Freestanding Mount. Also available as a Wall Mounted Unit or with a Table stand.



+ 353 1 620 5501



Unit 3 - 5, Block K, Grants Rd,  
Greenogue Industrial Estate,  
Rathcoole, Co. Dublin, D24 TY43.

+353 1 620 5501  
sales@emscopiers.ie  
www.emscopiers.ie



## Key Features



### Temperature alarm

Equipped with an optional abnormal temperature alarm. Voice alarm volume customisation will accommodate louder environments, such as construction sites and factories.



### Works with protective masks

Recognition technology enable detection with or without PPE. Works on individuals both with and without a protective face mask over their mouths.



### Recording Enabling Available

Enable the video recording to record every user. Recorded images confirm date/time/photo of the each user which can be extracted from device via username/password. Manual Extraction assists in compliance with GDPR regulations.



# Technical Specification

Camera	Pixel	200W pixels
	Type	RGB Infrared dual camera
	Aperture	F2.4
	Focal Distance	50-150cm
	White Balance	Automatically
	Fill Light	LED & Infrared double fill light
Screen	Size	8.0 inch IPS LCD
	Resolution	Screen 800x1280
	Touch Sensor	No
Processor	CPU	RK3288 Quad-Core
	Local storage	EMMC 8G
Ports	Internet	Ethernet, Wi-Fi
	Audio	2.5W/4R horn
	USB ports	USB x 2 HOST standard A
	Serial - communication	RS232 x 1
	Relay output	1 single output
	Wiegand interface	26/34output x 1 26/34input x 1
	Upgrade button	Leave the Uboot upgrade button on the device line
	Wired Network	RJ45 x 1
Face Detection	Face library support	Up to 30,000
	1 : N Face recognition	YES
	1 : 1 Face comparison	YES
	Stranger detection	YES
	Identify distance configuration	YES
	UI interface configuration	YES
	Device Ports	Equipment management, personnel / photo management, record query, etc.
Infrared Thermal Imaging Module	Deployment method	Supports public cloud deployment, privatized deployment, LAN use
	Temperature detection	Yes
	Temperature detection distance	1 meter ( $\leq 0.5$ meter)
	Temperature measurement accuracy	$\leq +/- 0.2^{\circ}\text{C}$
	Temperature measurement range	$10^{\circ}\text{C} - 42^{\circ}\text{C}$
	Thermal Field of View	32 X 32 $^{\circ}\text{C}$
Normal temperature release	Yes	